

WrapTec is available in two colours: anthracite and light-grey.
Rolls are available in 10 m length and multiple widths.



PRODUCT DATA

Material	High performance polymer (Polyisobutylene)
Application	Cladding / jacketing / sealing of HVAC ducts, pipes and technical insulations
Widths	70mm, 140mm, 280mm, 560mm
Length	10m per roll
Colours	anthracite, light-grey
Application temperature	+5 °C up to +40 °C
Heat resistance	-40 °C up to +100 °C
Fire class	E (B2) (DIN EN ISO 11925-2 / DIN EN ISO 13501-1/ DIN 4102)
Connections	By self-welding
Weight	ca. 1.85kg/m ² 1.31kg (per 70 mm roll) 2.63kg (per 140 mm roll) 5.25kg (per 280 mm roll) 10.50kg (per 560 mm roll)
Thickness	Ca. 1.05mm
Stability (UV)	DIN 16726 (DIN EN ISO 20811)
Water column	> 7.5 m (DIN EN ISO 20811)
Vapour permeability	S _v > 400m; μ > 400.000 (DIN EN ISO 1931)
Storage	Dry up to +40°C

For further information please contact:

Monier Roofing Components GmbH

Frankfurter Landstrasse 2-4

D-61440 Oberursel


wraptec@monier.com

www.wraptec.net



WRAPTEC®

Self-welding. Waterproof. Weatherproof.



Monier is committed to continuously enhancing and improving our product range. Monier reserves the right to change our product specifications and the right to correct any typographical or clerical error or omission.

© Monier Roofing Components GmbH

LF-EN-1216

Part of BRAAS MONIER BUILDING GROUP

WRAPTEC®

Quality and efficiency

WrapTec is a new material for sealings in the area of technical insulation. The unique self-welding characteristic allows fast and easy installations at any construction site. The high performance material provides extreme UV stability and weather resistance in all environments. Due to its absolute water and humidity tight sealing it prevents corrosion under insulation (CUI) at the duct pipe.



More than 20 years of proven sealing experience and know-how in the construction industry has led to this new innovative solution.



Product advantages

Innovative and reliable

WrapTec

- is 100 % watertight
- is self-welding
- is extreme UV- and weather resistant
- Saves up to 50 % of labour costs compared to other installation coverings. Is easy and fast to install (requires no tools apart from scissors)
- Protects the duct work from corrosion under insulation (CUI)
- Offers various opportunities for usage due to environmental friendly recipe
- Saves storage costs and simplifies transport to and on building sites

An overlap of only 20mm is sufficient in order to provide protection to the insulation and duct system itself. WrapTec can be stretched by 50 % in all directions to ensure a proper and aesthetic installation.



The high performance material ensures environmental friendliness for all usage areas. The material is 100 % recyclable.

